



SAFETY DATA SHEET
FIXT SILICONE SEALANT CLEAR

Page: 1

Compilation date: 07/04/2014

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FIXT SILICONE SEALANT CLEAR

Product code: FX085529

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Silicone elastomer.

1.3. Details of the supplier of the safety data sheet

Company name: Quest Consumables Ltd

Stock House

Seymour Road

Nuneaton

Warwickshire

CV11 4LB

UK

Tel: +44 (0) 2476 322126

Fax: +44 (0) 2476 3221174

Email: sales@questconsumables.com

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P264: Wash contaminated skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

[cont...]

SAFETY DATA SHEET

FIXT SILICONE SEALANT CLEAR

Page: 2

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+313: If skin irritation occurs: Get medical attention.

P337+313: If eye irritation persists: Get medical attention.

P362: Take off contaminated clothing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TRIACETOXY(ETHYL)SILANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
241-677-4	17689-77-9	-	Skin Corr. 1B: H314	1-10%

GASOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

265-148-2	64742-46-7	-	-	1-10%
-----------	------------	---	---	-------

METHYLTRIACETOXYSILANE

-	4253-34-3	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335	1-10%
---	-----------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: If conscious, give half a litre of water to drink immediately. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

[cont...]

SAFETY DATA SHEET

FIXT SILICONE SEALANT CLEAR

Page: 3

5.1. Extinguishing media

Extinguishing media: On large fires use dry chemical, foam or water spray (fog). On small fires, use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. In combustion releases toxic fumes of formaldehyde

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Avoid skin and eye contact.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is exhaust ventilation of the area. Do not breathe vapour. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid exposure. Wash after handling, especially before eating, drinking or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store away from oxidizing agents. Avoid contact with water or humidity.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET

FIXT SILICONE SEALANT CLEAR

Page: 4

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. No respiratory protection should be needed with good local ventilation.

Hand protection: Chemical protective gloves should be worn: Butyl gloves. Nitrile gloves. Neoprene gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective equipment is not normally necessary.

Environmental: Refer to sections 6 and 12.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Acetic acid.

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: No data available.

Boiling point/range°C: No data available.

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: > 100

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 1.01

pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Cures in the presence of water or moisture, releasing a small amount of acetic acid.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET

FIXT SILICONE SEALANT CLEAR

Page: 5

10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: None known

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Water.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Silicon dioxide. Formaldehyde.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Solid material, insoluble in water. No adverse effects are predicted.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET
FIXT SILICONE SEALANT CLEAR

Page: 6

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste authorities.

Disposal of packaging: Dispose of in accordance with local regulations.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.